# **ANTENNA TUNER**

# 3046







# **KEY FEATURES**

- · Fast tuning
- · High efficiency
- Waterproof
- MIL-STD-810G compliance
- 2 to 30 MHz
- 125 W RF power handling
- Suits antennas up to 9 m
- Flexible mounting
- ALE, 36 ALE, and frequency hopping compatibility
- · Internal receive mode amplifier

The 3046 is a low profile, 125 W HF antenna tuning unit designed to deliver high performance and reliability in the world's harshest environments. It provides high speed and efficient tuning of short and long whip antennas across the full operational HF band.

# **HIGH PERFORMANCE**

With a 125 W RF power handling capability, the 3046 can be used for voice (including frequency hopping) and data operation over the full 2 to 30 MHz frequency band. The tuner has an unlimited tune from memory capacity, and using a state-of-the-art tuning algorithm, new frequencies are tuned in typically less than one second.

The 3046's innovative circuit design ensures power delivery to the antenna is maximised, and receive mode performance is optimised by the internal receive mode amplifier. These features combine to provide an easy-to-use, trouble-free, high performance mobile antenna solution.

## **COMPLIANT TO MIL-STD-810G**

The high strength and lightweight alloy housing of the 3046 ensures that it is capable of withstanding the severe environmental conditions encountered in mobile environments. The unit is designed to meet MIL-STD-810G for dust and vibration and is waterproof to 1 m as per IP68 Standard.

# TRANSCEIVER INTEGRATION

The control interface of the 3046 is fully integrated with Codan's HF transceivers so that tuning is transparent to the operator. If there is a tune problem, the transceiver issues an audible and visual warning, however an override capability exists for emergency situations. The 3046 is designed for full compatibility with all modes of operation, including receiver scanning, ALE (Automatic Link Establishment) and frequency hopping.

### ANTENNA & MOUNT OPTIONS

The 3046 is offered with a 3 m carbon fiber MIL spec whip antenna, MIL spec rubber spring and NATO hole pattern base. The 3 m whip can be configured for NVIS operation using the tie down kit included and can also be extended to 7 m with the 3 section Extension and Guy Kit for semi-permanent stationary use. An additional antenna accessory is the 9 m tactical long wire kit designed to attach directly to the NATO base stud.







# **ANTENNA TUNER** 3046



SPECIFICATIONS	
GENERAL	
Frequency range	2 to 30 MHz (using 3 m or 7 m MIL spec whip or 9 m long wire antenna)
Power rating	125 W PEP
Power consumption	Typically 400 mA, less than 0.8 A maximum
Input impedance	50 Ω
VSWR	Typical ≤1.5:1
Tuning speed	New frequency <1 second average, memory tune <150 ms
Memory channels	Unlimited (unique non-linear memory allocation)
DC operating range	Codan transceiver (12 V nominal)
MECHANICAL	
Temperature	-30 to +60°C (-22 to +140°F), 95% humidity
Protection	Open Circuit, Short Circuit, Over Temperature, High VSWR
Environmental	MIL-STD-810G (Dust, Vibration) Immersion to IP68
EMC	Designed to MIL-STD-461
Dimensions	340 mm L x 210 m W x 95 mm H (13.4 in L x 8.3 in W x 3.7 in H)
Weight	2.4 kg (5.3 lbs)
Colour	White or olive drab green
INTERFACE	
RF connector	N-type socket
Control	6 pin bayonet (MIL spec)

Values noted are typical. Equipment descriptions and specifications subject to change without notice or obligation.

# **ACCESSORIES**

#### **Antennas**

- 3 m MIL spec two section whip (includes NVIS tie down kit)
- MIL spec, 3 section antenna extension and guy kit (extends standard 3 m antenna to 7 m)
- 9 m long wire antenna kit

### **Antenna bases**

- MIL spec rubber spring
- NATO hole pattern antenna base

#### **Mounting hardware**

- Vehicle shock mount
- Installation kit

### **Cables**

- 2, 6 10 and 20 m (6.6, 19.7, 32.8 and 65.6 ft) RF coaxial cables
- 2, 6 10 and 20 m (6.6, 19.7, 32.8 and 65.6 ft) control cable

DATASHEET: Codan 3046 HF Antenna Tuner, 12-20258-EN, Issue 4, © 2018

CODANCOMMS.COM